

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address COMMISSIONER FOR PATENTS PO Box 1450 Alcassedan, Virginia 22313-1450 www.emplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/724,775	12/02/2003	Cheng-Yin Lee	ALC 3100	1920
30868 KRAMER & A	7590 04/02/200 MADO P.C	EXAMINER		
1725 DUKE ST		MILLS, DONALD L		
SUITE 240 ALEXANDRIA, VA 22314			ART UNIT	PAPER NUMBER
	1, 7.1 22311		2416	•
			MAIL DATE	DELIVERY MODE
			04/02/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No. Applicant(s)			
Application No.			
10/724,775	LEE, CHENG-YIN		
Examiner	Art Unit		
DONALD L. MILLS	2416		

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS.

WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
- after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. Failure to repty within the set or extended period for repty will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).

 Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any

	eamed	patent te	rm adjustr	nent.	See 37	CFR	1.704(0).
C4-4	_						

Otatus	
1) Responsive to communication(s) filed on 05 Janua 2a) This action is FINAL. 2b) This action 3) Since this application is in condition for allowance closed in accordance with the practice under Ex part 1) Expansive Times Time	on is non-final. except for formal matters, prosecution as to the merits is
Disposition of Claims	
4) Claim(s) 1-37 is/are pending in the application. 4a) Of the above claim(s) 19-37 is/are withdrawn fro 5) Claim(s) is/are allowed. 6) Claim(s) 1-18 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or ele	
Application Papers	
9) The specification is objected to by the Examiner. 10) The drawing(s) filed on islane: a) accepter Applicant may not request that any objection to the draw Replacement drawing sheet(s) including the correction is 11) The oath or declaration is objected to by the Examin	ing(s) be held in abeyance. See 37 CFR 1.85(a). required if the drawing(s) is objected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119	
12) Acknowledgment is made of a claim for foreign prio a) All b Some c) None of: 1. Certified copies of the priority documents hat 2. Certified copies of the priority documents hat 3. Copies of the certified copies of the priority of application from the International Bureau (PC * See the attached detailed Office action for a list of the	we been received. we been received in Application No couments have been received in this National Stage TRule 17.2(a)).
Attachment(s)	
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patient Drawing Review (PTO-948) 3) Information Diselecture Statement(e) (PTO/SZ/CS) Paper Nots)/Mail Date	4) Interview Summary (PTO-413) Paper Nots/Mail Date. 5.) Neitice of Informal Patent Application. 6) Other:
.S. Patent and Trademark Office	

DETAILED ACTION

Claim Rejections - 35 USC § 102

 The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- Claims 1-18 are rejected under 35 U.S.C. 102(e) as being anticipated by Sing et al. (US 2003/0088698 A1), hereinafter referred to as Singh.

Regarding claims 1, 9, and 15, Singh discloses a VPN failure recovery for rapid failover of a communication path between computers that are linked by redundant virtual links in a virtual private network, which comprises:

A first hub node serving client equipment (CE) devices connected on a first ELAN, a spoke node serving CE devices on a second ELAN; a first point-to-point link L1 for interconnecting said first hub node and said spoke node; means for detecting a failure of said first point-to-point link L1, and for transmitting a corresponding failure notice; a second hub node interconnected with said first hub node, means for establishing a redundant point-to-point link L2 from said second hub node to said spoke node in response to said failure notice (Note, where means plus function language is used to define the characteristics of a machine or manufacture invention, such language must be interpreted to read on only the structures or materials disclosed in the specification and "equivalents thereof" that correspond to the recited

function. Referring to Figures 1 and 2, Communication between clients 110 (client equipment) and servers 160 passes through public network 130 over virtual links of a virtual private network (VPN) (ELAN). At the site of each client 110, an access device 120 is coupled on the communication path between client 110 and public network 130 (second ELAN). Each access device 120 establishes VPN tunnels 135 to two or more gateways 140 (first hub node and second hub node). Each tunnel makes use of the IPSec protocol to transport and encrypt packets passing between access devices 120 and gateways 140. Each IPSec tunnel carries a PPP (Point-to-Point Protocol) data stream that is transported using a GRE (Generic Routing and Encapsulation) protocol. In this way, each tunnel provides a virtual link between the access device 120 and the gateway 140 at its endpoints. Different tunneling protocols, such as native IPSec tunneling, or L2TP or PPTP based tunnels are used to link the access devices and the gateways, and combinations of different tunneling protocols are used to link different clients to the servers. See paragraph 0055. Following link failures, communication from the tunnel 135 linking access device 120A and primary gateway 140A to the tunnel 135 linking access device 120A and backup gateway 140B. For example, if client 110A (means for detecting a failure) had active transport layer sessions with both server 160A and 160B (illustrated as paths 210), then after the failover, these transport sessions follow paths through backup gateway 140B (means for establishing a point-to-point link. See paragraph 0059.)

Regarding claims 2 and 13, Singh discloses wherein said second hub node operates as a spoke node of first said hub node under based on an absence of failure notice (Referring to Figures 1 and 2, following link failures, communication from the tunnel 135 linking access device 120A and primary gateway 140A to the tunnel 135 linking access device 120A and

Application/Control Number: 10/724,775

Art Unit: 2416

backup gateway 140B (which operates as a node of the primary gateway under normal conditions). For example, if client 110A had active transport layer sessions with both server 160A and 160B (illustrated as paths 210), then after the failover, these transport sessions follow paths through backup gateway 140B). See paragraph 0059.)

Regarding claims 3 and 14, Singh discloses wherein said first hub node is capable of operating as a spoke node of said second hub node when said first hub node fails (Referring to Figures 1 and 2, following link failures, communication from the tunnel 135 linking access device 120A and primary gateway 140A (capable of operating as a spoke node of the backup gateway when the primary gateway fails) to the tunnel 135 linking access device 120A and backup gateway 140B. For example, if client 110A had active transport layer sessions with both server 160A and 160B (illustrated as paths 210), then after the failover, these transport sessions follow paths through backup gateway 140B. See paragraph 0059.)

Regarding claims 4 and 12, Singh discloses wherein said means for detecting a failure of said first point-to-point link L1 is a first PE node interfacing said first hub with said service provider network monitors said first link L1 for detecting a failure at said hub node (Referring to Figures 1-3, Each access device 120 (PE node) has a similar logical arrangement as that shown for gateway 140 in FIG. 3. A heartbeat module in an access device sends heartbeats to the gateways 140 to which it has tunnels. If the primary gateways fails to respond (layer 1 signaling protocol), the access device terminates the tunnel and the router module immediately starts passing packets from client 110 over a tunnel 135 to a backup gateway 135. The tunnel module then begins and continues to try to reestablish a tunnel to the primary gateway. The router module at the access device sends a request to the router module at the backup gateway to send

updated routing information rather than waiting to periodic routing updates it would send as part of normal operation of the route update protocol. See paragraph 0064.)

Regarding claims 5, 10, and 11, Singh discloses wherein said establishing a redundant point-to-point link L2 in response to said failure notice includes said first PE node signaling said second PE node to establish a second point-to-point link with said second hub node, and to remap the traffic from said second hub node over said second point-to-point link and, in response, said second PE node establishes the second point-to-point link with said second hub node, and re-maps the traffic from said second hub node over said second point-to-point link (Referring to Figures 1-3 and 5C, a heartbeat failure from an access device 120 to a gateway 140 results in the following sequence of events. Access device 120 detects a heartbeat failure. The access device terminates the tunnel if it has not already been terminated (for example by the gateway under the scenario shown in FIG. 5B). At each access device 120 that has had the tunnel to its primary gateway terminated, the router module begins rerouting traffic to the backup gateway. The access device also request updated routing information from the backup gateway. The backup gateway sends the updated routing information in response to the request from the access device. After any tunnel to an access device is terminated, the access device begins to try to reestablish the tunnel. However, the gateway that terminated the tunnel does not accept the requests to reestablish the tunnels until it is one again successfully receiving replies to the heartbeat messages it is sending to servers 160. In various examples of this approach, private network 150 can include a variety of different types of routing "fabrics." For example, private network 150 can be configured to be statically routed or to use a dynamic routing protocol such as OSPF. See paragraphs 0078-0082.)

Regarding claims 6 and 16, Singh discloses wherein the access link between said spoke node and said second PE node is an aggregated bundle of links comprising a redundant link (Referring to Figures 1-3 and 5C, a heartbeat failure from an access device 120 to a gateway 140 results in the following sequence of events. Access device 120 detects a heartbeat failure. The access device terminates the tunnel if it has not already been terminated (for example by the gateway under the scenario shown in FIG. 5B). At each access device 120 that has had the tunnel to its primary gateway terminated, the router module begins rerouting traffic to the backup gateway. The access device also request updated routing information from the backup gateway. The backup gateway sends the updated routing information in response to the request from the access device. After any tunnel to an access device is terminated, the access device begins to try to reestablish the tunnel (aggregated bundle of links comprising a redundant link). See paragraphs 0078-0082.)

Regarding claims 7 and 17, Singh discloses wherein connectivity between said second PE node and said spoke node is maintained when a link on said respective aggregated bundle is interrupted (Referring to Figures 1-3 and 5C, a heartbeat failure from an access device 120 to a gateway 140 results in the following sequence of events. Access device 120 detects a heartbeat failure. The access device terminates the tunnel if it has not already been terminated (for example by the gateway under the scenario shown in FIG. 5B). At each access device 120 that has had the tunnel to its primary gateway terminated, the router module begins rerouting traffic to the backup gateway. The access device also request updated routing information from the backup gateway. The backup gateway sends the updated routing information in response to the request from the access device. After any tunnel to an access device is terminated, the access

Application/Control Number: 10/724,775

Art Unit: 2416

device begins to try to reestablish the tunnel (connectivity is maintained when a link of the respective bundle is interrupted). See paragraphs 0078-0082.)

Regarding claims 8 and 18, Singh discloses wherein the loss of a link in said aggregated bundle is transparent to said spoke node (Referring to Figures 1-3 and 5C, a heartbeat failure from an access device 120 to a gateway 140 results in the following sequence of events. Access device 120 detects a heartbeat failure. The access device terminates the tunnel if it has not already been terminated (for example by the gateway under the scenario shown in FIG. 5B). At each access device 120 that has had the tunnel to its primary gateway terminated, the router module begins rerouting traffic to the backup gateway. The access device also request updated routing information from the backup gateway. The backup gateway sends the updated routing information in response to the request from the access device. After any tunnel to an access device is terminated, the access device begins to try to reestablish the tunnel (the loss of a link is transparent because the path is rerouted and service is not interrupted). See paragraphs 0078-0082.)

Response to Arguments

 Applicant's arguments filed 05 January 2009 have been fully considered but they are not persuasive.

Rejection Under 35 U.S.C. 102

On page 14 of the remarks, regarding claims 1-18, the Applicant argues Singh does not disclose all of the claim limitations of claims 1 and 9. The Examiner respectfully disagrees. The Applicant states the elements of Singh are not taught by Singh because the reference does not

utilize the exact language of the claims. However, the Applicant fails to set forth whether the claims functionally or structurally differ from the network of Singh. The Applicant's arguments fail to comply with 37 CFR 1.111(b) because they amount to a general allegation that the claims define a patentable invention without specifically pointing out how the language of the claims patentably distinguishes them from the references. Singh discloses a functionally and structurally equivalent virtual redundant links in a virtual private network. Therefore, all of the claim limitations are disclosed.

Conclusion

4. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

5. Any inquiry concerning this communication or earlier communications from the

examiner should be directed to DONALD L. MILLS whose telephone number is (571)272-3094.

The examiner can normally be reached on 9:00 AM to 5:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Chi Pham can be reached on 571-272-3179. The fax phone number for the

organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would

like assistance from a USPTO Customer Service Representative or access to the automated

information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Donald L Mills/ Examiner, Art Unit 2416

March 30, 2009